

PP Acrylic 28my NN AC 822NN

DESCRIPTION

High-grade water based no noise acrylic tape. Carrier BOPP 28my film, with 24my adhesive for manual carton sealing packaging applications. No noise properties.

PRODUCT APPLICATION

- Manual carton sealing
- Adhesion on uneven surfaces due to high amount of adhesive
- Particularly suitable for all sorts of packaging applications
- Suitable for cold and hot temperatures

PRODUCT PROPERTIES

- Environmentally friendly and ecological adhesive
- Moisture compatible after application
- UV resistant adhesive
- Resistance to temperature changes
- Longevity of application

TECHNICAL DATA SHEET

NOMINAL VALUES

Backing Biaxially Oriented Polypropylene

(BOPP)

Acrylic (Water-based) **Adhesive**

Tensile Strength $140 \pm 30 \, (N/mm^2)$

TM 5004 by Afera

Elongation at Break $140 \pm 30 \ (\%)$

TM 5004 by Afera

Adhesion to Steel $6.0 \pm 1 \, (N/25 mm)$

TM 5001 by Afera

Over 180 (h, 25mm x 25mm **Shear to Steel**

TM 5012 by Afera on stainless steel, 23°C)

Rolling Ball Tack Under 3 (cm) PSTC-6 (PSTC)

Film thickness $28 \pm 1 \text{ (mic)}$

Transparent Z **Film Colors**

Transparent Brown **Adhesive Color**

White 2



Athens: 68, Varis Avenue, 166 73 Voula, Greece, Tel.: +30 210 899 5388, Fax exports: + 30 210 899 5386 Factory: 3rd km Pr. rd Skala - Atalanti, 352 00 Atalanti, Greece, Tel.: +30 223330 23725, Fax exports: + 30 22330 23756

info@atlas-tapes.gr, www.atlas-tapes.gr

The following data are nominal values based on PSTC, Afera and other standard tests. Information herein is only for general guidance and does not guarantee for accuracy and completeness. The user must, by test or otherwise, determine suitability for this product. Our standard term and conditions of safe apply exclusively to all orders, and all liability for damages of any kind, is limited to the amount of product. We reserve the right to make changes without notice or obligation in our products and publications.



EFFECTIVE: April 2014