



**ATLAS
TAPES**

PVC 335-37my colored PV 804

TECHNICAL DATA SHEET

DESCRIPTION:

Solvent based natural rubber tape VC 35-37mic colored film, suitable for printing with ordinary flexographic printing machine, without use of primer and release.

APPLICATIONS:

- Ease of print with standard flexographic machines without use of primer and release.
- Manual carton sealing
- Adhesion on uneven surfaces due to excellent adhesive power.
- Suitable for all sorts of packaging applications.
- Suitable for use on most types of recyclable cartons, due to special adhesive compound.

PROPERTIES:

- Completely silent
- Hand tear able
- Excellent printability properties to satisfy the most demanding printing application
- Resistant to temperature changes
- Moisture compatible after application
- Longevity of application
- Excellent adhesive power.

ATHENS
68 Varis Avenue
16673 Voula, Greece
Tel.: +30 210 8995388

ATALANTI
3rd km Skala Atalanti Road
35200 Atalanti, Greece
Tel.: +30 22330 23725

www.atlas-tapes.gr
info@atlas-tapes.gr

ALL ABOUT TAPES



NOMINAL VALUES:

Backing
PVC

Adhesive
Solvent-based, Natural Rubber

Tensile Strength MD
150 ± 30 (N/mm²)
TM 5004 by Afera

Elongation at Break MD
75 ± 30 (%)
TM 5004 by Afera

Adhesion to Steel
4 ± 1 (N/25mm)
TM 5001 by Afera

Shear to Steel
Over 200 (h, 25mm x 25mm on stainless steel, 23°C)
TM 5012 by Afera

Rolling Ball Task
Under 3 (cm)
PSTC-6 (PSTC)

Film thickness
35-37 ± 10% (mic)

Film Colors

Red ■ Yellow ■ Light Green ■ Light Blue ■
Orange ■ Dark Green ■ Dark Blue ■

Adhesive Color

White